



# Altro Wood™ adhesive-free

safety flooring



1000 x 125 mm

Portuguese Oak | AFW280013  
WR335 / A1M335 / LRV 51



500/500 x 100 mm

Frosted Oak | AFW280001  
WR335 / A1M335 / LRV 52



500/500 x 100 mm

Timeless Oak | AFW280007  
WR347 / A1M347 / LRV 38



**Altro adhesive-free flooring** - swatch shows underside emboss of Altro Wood adhesive-free.  
Reusable and recyclable post-use.



500/500 x 100 mm

Post Oak | AFW280016  
WR350 / A1M483 / LRV 30



500/500 x 100 mm

Champagne Oak | AFW280010  
WR338 / A1M338 / LRV 38



500/500 x 100 mm

Summer Oak | AFW280005  
WR340 / A1M340 / LRV 37



500/500 x 100 mm

Caramel Oak | AFW280006  
WR353 / A1M225 / LRV 25




550/450 x 100 mm

Honey Maple | AFW280011  
WR352 / A1M352 / LRV 27



500/500 x 100 mm

Birnam Oak | AFW280017  
WR352 / A1M352 / LRV 21



550/450 x 100 mm

Imperial Walnut | AFW280009  
WR341 / A1M160 / LRV 15



550/450 x 100 mm

Soft Maple | AFW280002  
WR339 / A1M339 / LRV 24



500/500 x 100 mm

Bur Oak | AFW280015  
WR514 / A1M514 / LRV 21



550/450 x 100 mm

Shaded Cherry | AFW280004  
WR337 / A1M337 / LRV 17



1000 x 125 mm

Oxford Oak | AFW280014  
WR339 / A1M339 / LRV 22



550/450 x 100 mm

Holm Oak | AFW280018  
WR478 / A1M390 / LRV 26



550/450 x 100 mm

Dusky Cherry | AFW280003  
WR336 / A1M239 / LRV 22



1000 x 125 mm

Vintage Oak | AFW280012  
WR322 / A1M239 / LRV 19



500/500 x 100 mm

Pitch Oak | AFW280008  
WR348 / A1M348 / LRV 7




















Dimensions indicate plank size within roll design.



## Typical applications

Bedrooms in care homes and hotels. Receptions, corridors, general circulation and public areas in hospitals, care homes, kindergartens and schools. Wards, waiting and treatment rooms in hospitals and care homes. As an alternative to LVTs in student accommodation. Common rooms, staff rooms in schools. Café, dining areas.

## Technical information

	Fire behaviour tested in acc. with Classified in acc. with	EN ISO 9239-1 EN ISO 11925-2 EN 13501-1	≥ 4.5 kW/m <sup>2</sup> Pass C <sub>f</sub> -s1
	Slip resistance	EN 13893 PTV DIN 51130 / BGR 181 EN 13845 Annex C	≥ 0.30 / DS ≥ 36 R10 ESf
	Sound insulation	EN ISO 10140	ca. 14 dB
	Flooring type	EN 651	Safety flooring
	Thickness	EN ISO 24346	2.4 mm
	Wear layer thickness	EN ISO 24340	0.7 mm
	Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m <sup>2</sup>
	Weight	EN ISO 23997	2.4 kg/m <sup>2</sup>
	Residual indentation	EN ISO 24343-1	≤ 0.20 mm
	Classification for use	EN ISO 10874	34, 42
	Flexibility	EN ISO 24344	Pass
	Dimensional stability	EN ISO 23999	≤ 0.4 %
	Light fastness	EN ISO 105-BO2	≥ 6
	Castor chair abrasion	EN 425	Yes, type W
	Wear resistance	EN 660-2	Group T
	Chemical resistance	EN ISO 26987	Good
	Under floor heating	EN 12524	Suitable
	Electrical behaviours	EN 1815	≤ 2 kV, antistatic
	VOC emissions	CDPH 1350 / Floorscore Indoor Air Comfort Gold	Approved Approved



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



20 | debolon dessauer bodenbeläge GmbH & Co. KG.  
Ebertallee 209, D-06846 Dessau-Roßlau | EN 651 |  
DOP-No. RN-A034 | Reaction to fire: Cl-s1 | Slip resistance: DS |  
Formaldehyde: E1 | Electrical behaviour: EN 1815 < 2 kV |  
EN 14041:2004/FAC:2006 | 1658 |  
Resilient floor covering to be used within a building



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



## Sustainability



\*A+ BRE generic green guide rating for resilient flooring, full details available at [www.thegreenguide.org.uk](http://www.thegreenguide.org.uk)

## Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance. Technical information on installation and staining can be found at [www.altro.com](http://www.altro.com)

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed. Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value

 Altro, Designed for possibilities. Made for people. Altro Wood and Altro Easyclean technology are trademarks of Altro Limited.

United Kingdom

+44 (0) 1462 707 700

[enquiries@altro.com](mailto:enquiries@altro.com)

Australia

+61 3 9764 5666

[info@asf.com.au](mailto:info@asf.com.au)

Subject to alteration.