





# Altro Marine™ 20 / T20


Like Altro Marine?  
Love Altro's shoe  
and barefoot ranges



Steam | IPT20807  
WR85 / A1M85 / LRV 37



Rainfall | IPT20810  
WR135 / A1M135 / LRV 38



Cascade | IPT20809  
WR105 / A1M01 / LRV 71




Gull | T20813  
WR79 / A1M191 / LRV 46




Marlin | T20811  
WR203 / A1M203 / LRV 34




Reef | T20801  
WR20 / A1M20 / LRV 41



Shark | IPT20812  
WR201 / A1M84 / LRV 24



Tide | IPT20808  
WR71 / A1M71 / LRV 21



Seagrass | IPT20814  
WR137 / A1M137 / LRV 37

Love Altro's shoe and barefoot ranges


**Altro Aquarius**

**Altro Pisces**



Request your Altro Aquarius™ or Altro Pisces™ sample card now

+44 (0) 1462 707 700 [samples@altro.com](mailto:samples@altro.com)






















Fen | IPT20815  
WR242 / A1M242 / LRV 19



## Typical applications

Shower cubicles. Swimming pool foot bath. Swimming pool surrounds.

## Technical information

	Fire behaviour tested in acc. with	EN ISO 9239-1 EN ISO 11925-2 EN 13501-1	≥ 8 kW/m <sup>2</sup> Pass B <sub>f</sub> -s1
	Slip resistance	EN 13893 EN 13845 Annex C EN 16165 Annex B / ASR A1.5 EN 16165 Annex A	≥ 0.30 / DS ESb R10 C
	Sound insulation	EN ISO 140-8	ca. 13 dB
	Flooring type	EN 13845	Safety flooring
	Thickness	EN ISO 24346	2 mm
	Wear layer thickness	EN ISO 24340	2 mm
	Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m <sup>2</sup>
	Weight	EN ISO 23997	2.8 kg/m <sup>2</sup>
	Residual indentation	EN ISO 24343-1	≤ 0.10 mm
	Classification for use	EN ISO 10874	34, 43
	Flexibility	EN ISO 24344	Pass
	Dimensional stability	EN ISO 23999	≤ 0.4 %
	Light fastness	EN ISO 105-B02	≥ 6
	Castor chair abrasion	ISO 4918	Yes, type W
	Wear resistance	EN 13845 Annex D	≤ 10% / 50000 cycles
	Chemical resistance	EN ISO 26987	Good
	Underfloor heating	EN 12524	Suitable
	Electrical behaviours	EN 1815	≤ 2 kV, antistatic
	VOC emissions	CDPH 1350 / Floorscore	Approved



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



1029  
EN 14041



0120  
EN 14041



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



## Sustainability



†A+ BRE generic green guide rating for resilient flooring, full details available at [www.thgreenguide.org.uk](http://www.thgreenguide.org.uk)



EN 15804 SD207  
EPD No.: 000255



## Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance. Technical information on installation and staining can be found at [www.altro.com](http://www.altro.com)

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed.

Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value

Request your Altro Aquarius or Altro Pisces sample card now – ☎ 01462 707 700 ✉ [samples@altro.com](mailto:samples@altro.com)

 Altro, Altro Marine, Altro Aquarius, Altro Pisces and Altro EasyClean Technology are trademarks of Altro Limited.

United Kingdom

☎ +44 (0) 1462 707 700

✉ [enquiries@altro.com](mailto:enquiries@altro.com)

Australia

☎ +61 3 9764 5666

✉ [info@asf.com.au](mailto:info@asf.com.au)